PJ1 UNO | Rörstativ

Modellserie 175-850 mm | Maximal belastning 450 kg per stativ

Rörstativ med enkel pelare och V-format stödhuvud för stöd av rör vid arbete på låg höjd i verkstad. Enkelt att ställa upp och använda. Fem modeller ger olika höjdintervall. Utvalda rullsatser och kulrullar från PJ3-serien kan monteras på V-huvudet.



Modeller och arbetshöjder

Modell	Min./max. höjd (mm)	Maximal belastning (kg)
PJ1-1	175-260	450
PJ1-2	250-400	450
PJ1-3	400-550	450
PJ1-4	550-700	450
PJ1-5	700-850	450

175-850 mm är seriens sammanlagda höjdområde. Varje modell justeras inom sitt eget angivna intervall. Specialstorlekar finns på förfrågan.

Rullsatser och kulrullar som tillval

Artikel	Utförande	Satsens kapacitet (kg)	Satsens vikt (kg)
SWK3	Stålrullar	1000	3,4
SWK3SS	Rostfria stålrullar	1000	3,4
NWK3	Nylonrullar	450	2
PWK3	Polyuretanrullar	600	4
BTK3	Kulrullar, stål	600	2,5
BTK3SS	Kulrullar, rostfritt stål	600	2,5

Samtliga listade satser: rördiameter 25,4-304,8 mm. Tillbehörens kapacitet höjer inte PJ1-stativets maxlast: hela kombinationen är begränsad till 450 kg per stativ.



Stålrullar



Nylonrullar



Kulrullar

PJ1 UNO | Pipe stand

Model range 175-850 mm | Maximum load 450 kg per stand

Single-column pipe stand with a V-head for supporting pipes during low-level workshop work. Simple to set up and use. Five models provide different height ranges. Selected PJ3-series wheel and ball transfer kits can be fitted to the V-head.



Models and working heights

Model	Min./max. height (mm)	Maximum load (kg)
PJ1-1	175-260	450
PJ1-2	250-400	450
PJ1-3	400-550	450
PJ1-4	550-700	450
PJ1-5	700-850	450

175-850 mm is the combined range of the series. Each model is adjustable only within its own listed range. Custom sizes are available on request.

Optional wheel and ball transfer kits

Article	Type	Kit rating (kg)	Kit weight (kg)
SWK3	Steel wheels	1000	3.4
SWK3SS	Stainless steel wheels	1000	3.4
NWK3	Nylon wheels	450	2
PWK3	Polyurethane wheels	600	4
BTK3	Ball transfers, steel	600	2.5
BTK3SS	Ball transfers, stainless steel	600	2.5

All listed kits: pipe diameter 25.4-304.8 mm. Kit ratings do not increase the PJ1 stand capacity: the complete assembly remains limited to 450 kg per stand.



Steel wheels



Nylon wheels



Ball transfers