PJ3 | Höjdjusterbara rörstativ

Tre ben | Arbetshöjd 710-1 220 mm | Maximal belastning 1 000 kg

PJ3 ger stöd åt rör vid svetsning, kapning och montering. Rörstativet är byggt i boxprofil och finns med fasta eller fällbara ben samt flera stödhuvuden, rullar och kulrullar.



Egenskaper

- Höjdjustering: 710-1 220 mm
- Fast eller fällbart stativ
- Fällbara ben förenklar transport och förvaring
- Flera typer av stödhuvuden
- Oberoende belastningsprovning

Grundstativ

Artikel	Benutförande	Vikt (kg)	Rör-Ø (mm)
PJ3FXB	Fasta	7,0	≤ 304,8
PJ3FLB	Fällbara	7,0	≤ 304,8

Litet V-huvud, rullsatser och rullhuvuden

Artikel	Utförande	Last (kg)	Vikt (kg)	Rör-Ø (mm)
PJ3V	Litet V-huvud	1 000	3,4	≤ 304,8
SSC3-1	Rostfria skyddshylsor	1 000	1	25,4-304,8
SWK3	Stålrullar	1 000	3,4	25,4-304,8
SWK3SS	Rostfria stålrullar	1 000	3,4	25,4-304,8
NWK3	Nylonrullar	450	2	25,4-304,8
PWK3	Polyuretanrullar	600	4	25,4-304,8
BTK3	Kulrullar, stål	600	2,5	25,4-304,8
BTK3SS	Kulrullar, rostfritt	600	2,5	25,4-304,8
SWK350	Rullhuvud, stål	1 000	4,9	25,4-304,8
SWK350SS	Rullhuvud, rostfritt	1 000	3,4	25,4-304,8
NWK350	Rullhuvud, nylon	450	4,9	25,4-304,8
PWK350	Rullhuvud, polyuretan	600	5	25,4-304,8

Maximal belastning beror på valt huvud eller rullsats. Överskrid inte belastningsgränsen för den komponent som har lägst kapacitet.

PJ3 | Stort V-huvud och tillbehör

Välj stödhuvud och rullsats efter rörets diameter, material och belastning. Tabellen visar respektive tillbehörs kapacitet och dimensioner.

Artikel	Utförande	Last (kg)	Vikt (kg)	Rör-Ø (mm)
LVH	Stort V-huvud	1 000	7,6	≤ 609,6
SSC4	Rostfria skyddshylsor	1 000	1	≤ 609,6
SWK4	Stålrullar	1 000	3	25,4-609,6
SWK4SS	Rostfria stålrullar	1 000	3	25,4-609,6
NWK4	Nylonrullar	450	1,8	25,4-609,6
PWK4	Polyuretanrullar	600	11,5	101,6-914,4
BTK4	Kulrullar, stål	600	2,3	25,4-609,6
BTK4SS	Kulrullar, rostfritt	600	2,3	25,4-609,6

Polyuretanrullarna PWK4 har dimensionsområdet 101,6-914,4 mm. Övriga dimensionsområden anges separat ovan. Rördimensionerna är omräknade till mm och alla vikter anges i kg.

Stödhuvuden och rullalternativ



Litet V-huvud



Stort V-huvud



Stålrullar



Kulrullar



Rullhuvud, nylon



Rullhuvud, polyuretan

PJ3 | Height-adjustable pipe stands

Three legs | Working height 710-1 220 mm | Maximum load 1 000 kg

PJ3 provides support for pipes during welding, cutting and assembly. The box-section stand is available with fixed or folding legs and a choice of heads, rollers and ball transfers.



Features

- Height adjustment: 710-1 220 mm
- Fixed or folding base
- Folding legs simplify transport and storage
- Choice of support heads
- Independently load tested

Base units

Article	Leg type	Weight (kg)	Pipe Ø (mm)
PJ3FXB	Fixed	7.0	≤ 304.8
PJ3FLB	Folding	7.0	≤ 304.8

Small V-head, wheel kits and roller heads

Article	Type	Load (kg)	Weight (kg)	Pipe Ø (mm)
PJ3V	Small V-head	1000	3.4	≤ 304.8
SSC3-1	Stainless steel sleeves	1000	1	25.4-304.8
SWK3	Steel wheels	1000	3.4	25.4-304.8
SWK3SS	Stainless steel wheels	1000	3.4	25.4-304.8
NWK3	Nylon wheels	450	2	25.4-304.8
PWK3	Polyurethane wheels	600	4	25.4-304.8
BTK3	Ball transfers, steel	600	2.5	25.4-304.8
BTK3SS	Ball transfers, stainless	600	2.5	25.4-304.8
SWK350	Roller head, steel	1000	4.9	25.4-304.8
SWK350SS	Roller head, stainless	1000	3.4	25.4-304.8
NWK350	Roller head, nylon	450	4.9	25.4-304.8
PWK350	Roller head, polyurethane	600	5	25.4-304.8

Maximum load depends on the selected head or wheel kit. Do not exceed the load rating of the lowest-rated component.

PJ3 | Large V-head and accessories

Select the support head and wheel kit to suit the pipe diameter, material and load. The table lists the capacity and dimensions of each accessory.

Article	Type	Load (kg)	Weight (kg)	Pipe Ø (mm)
LVH	Large V-head	1000	7.6	≤ 609.6
SSC4	Stainless steel sleeves	1000	1	≤ 609.6
SWK4	Steel wheels	1000	3	25.4-609.6
SWK4SS	Stainless steel wheels	1000	3	25.4-609.6
NWK4	Nylon wheels	450	1.8	25.4-609.6
PWK4	Polyurethane wheels	600	11.5	101.6-914.4
BTK4	Ball transfers, steel	600	2.3	25.4-609.6
BTK4SS	Ball transfers, stainless	600	2.3	25.4-609.6

PWK4 polyurethane wheels cover pipe diameters 101.6-914.4 mm. The other ranges are listed separately above. Pipe dimensions are converted to mm; all weights are in kg.

Support heads and roller options



Small V-head



Large V-head



Steel wheels



Ball transfers



Roller head, nylon



Roller head, polyurethane